



# SPRAYMASTER™ TANKS WITH PRO-AIR SYSTEM

SKID-MOUNTED SEALCOAT SPRAY SYSTEM APPLICATORS

DESIGNED TO MIX AND APPLY PAVEMENT SEALERS WITH OR WITHOUT SAND

### SprayMaster Features:

- Dependable, low-maintenance, air-driven dual diaphragm pump. Shifts to neutral automatically when wand or spray bar is shut off. Sprays sand-filled pavement sealers.
- Hydraulically controlled, full-sweep agitation with rubber wiper blades
- 75-foot hose and spray wand



**SPRAYMASTER SK 1500 WITH CUSTOM TRUCK MOUNTING**

AVAILABLE ON PAGE 53


PRODUCT #	DESCRIPTION	WEIGHT
E1320	SK 575 Pro-Air	2,240 lbs.
E1330	SK 750 Pro-Air	2,340 lbs.
E1340	SK 1,000 Pro-Air	3,200 lbs.
E1360	SK 1,500 Pro-Air	3,700 lbs.
E1370	SK 2,000 Pro-Air	4,200 lbs.

### Optional Features:


P50330	50 Gallon water tank, mounting kit and pump	
P50246M	Manual spray bar (includes seat and mounting components)	
P50331	Hydraulically driven SandPumper™ II material pump system	
P50246D	Hydraulically operated spray bar	
P50336	Electric Hose Reel: returns spray hose automatically	
P50337	Hand Operated Hose Reel	
P50403	Maxx-Air 2" Diaphragm Pump with 20 HP Compressor	
P50405	2" Air Diaphragm Pump	
P50281B	Night Work Lights	
E9100	Blocking / Bracing Charge (if required)	300 lbs.

\* Call for pricing | Components subject to change


### STANDARD FEATURES:



Honda GX390 Engine



Dual Diaphragm Material Pump



One Gallon Basket Strainer



75-foot Hose and Spray Wand

### SPECIFICATIONS:

Material Pump:  
 Type ..... Dual Diaphragm  
 Air Compressor:  
 Engine ..... Honda GX390  
 SCFM ..... 30.0

	575	750	1000	1500	2000
Height	60"	68"	76"	76"	76"
Width	48"	56"	64"	64"	64"
Length	144"	144"	144"	174"	204"