



# Safety Data Sheet

according to OSHA Hazard Communication  
29 CFR Part 1910.1200

## Section 1. Identification

**Product Information:** M1225P

**Product Name:** Acrylic Low VOC Yellow Traffic Marking Paint

**Recommended Use:** Liquid Paint

**Application Method:** Liquid Surface Paint

**Supplied by:** Thorworks Industries Inc.  
2520 S. Campbell St. Sandusky, OH 44870  
www.sealmaster.net | 1-800-326-199

**Emergency Telephone:** Chemtrec: 1-800-424-9300

## Section 2. Hazard(s) identification

**EMERGENCY OVERVIEW:** Flammable liquid and vapor.

### GHS Classification

Carc. 2, Flam. Liq. 2, STOT SE 3 NE, STOT SE 3 RTI

### Symbol(s) of Product



### Signal Word

Danger

### GHS ADDITIONAL INFORMATION

H362	Contains one or more Category 1 or Category 2 Reproductive Toxicants at greater than 0.1%. A Safety Data Sheet shall be available for the mixture upon request.
------	---

### GHS HAZARD STATEMENTS

Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
Carcinogenicity, category 2	H351	Suspected of causing cancer.

### GHS LABEL PRECAUTIONARY STATEMENTS

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.

P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor if you feel unwell.
P370+P378	In case of fire: Use dry chemical, carbon dioxide, or foam to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local rules and regulations.

#### GHS SDS PRECAUTIONARY STATEMENTS

P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.

### Section 3. Composition/Information on ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
ACETONE	67-64-1	10-25	GHS02-GHS07	H225-320-335-336
AROMATIC PETROLEUM DISTILATES	64742-94-5	1.0-2.5	GHS07-GHS08	H227-304-336-351
TOLUENE	108-88-3	1.0-2.5	GHS02-GHS07-GHS08	H225-304-315-319-336-361-373
METHANOL	67-56-1	0.1-1.0	GHS02-GHS06-GHS08	H225-301-311-319-331-360-370

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

### Section 4. First-aid measures



**FIRST AID - INHALATION:** Move to fresh air in case of accidental inhalation of vapors or decomposition products. Move to fresh air. Oxygen or artificial respiration if needed.

**FIRST AID - SKIN CONTACT:** If skin irritation persists, call a physician. Wash off immediately with soap and plenty of water. Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. Wash off with soap and water.

**FIRST AID - EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Rinse with plenty of water.

**FIRST AID - INGESTION:** Consult a physician. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

### Section 5. Fire-fighting measures

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Remove all sources of ignition.

**SPECIAL FIREFIGHTING PROCEDURES:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**EXTINGUISHING MEDIA:** Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam

### Section 6. Accidental release measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Soak up with inert absorbent material and dispose of as hazardous waste.

## Section 7. Handling and storage



**HANDLING:** Containers of this material may be hazardous when emptied. Handle in accordance with good industrial hygiene and safety practice.

**STORAGE:** Harmful - Store away from foodstuffs. Keep containers tightly closed. Keep in a well-ventilated place. Keep locked-up.

## Section 8. Exposure controls/personal protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
ACETONE	500	750	1000	NE
AROMATIC PETROLEUM DISTILATES	10	15	10	NE
TOLUENE	50	150	200	300
METHANOL	200	250	200	NE

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation  
Sk = Skin Sensitizer N.E. = Not Established

### Personal Protection



**RESPIRATORY PROTECTION:** In the case of respirable dust and/or fumes, use self-contained breathing apparatus.



**SKIN PROTECTION:** Impervious gloves.



**EYE PROTECTION:** Safety glasses with side-shields.



**OTHER PROTECTIVE EQUIPMENT:** Impervious clothing.



**HYGIENIC PRACTICES:** Contaminated work clothing should not be allowed out of the workplace. Keep working clothes separately.

## 9. Physical and Chemical Properties

<b>Boiling Range:</b>	56 - 485	<b>Vapor Density:</b>	4.00
<b>Odor:</b>	Characteristic	<b>Odor Threshold:</b>	NA
<b>Appearance:</b>	Heavy Yellow Liquid	<b>Evaporation Rate:</b>	14.40
<b>Solubility in Water:</b>	NE	<b>Specific Gravity:</b>	1.475
<b>Freeze Point:</b>	NE	<b>pH:</b>	NE
<b>Vapor Pressure:</b>	226.00	<b>Viscosity:</b>	NE
<b>Physical State:</b>	Liquid	<b>Flash Point, °C:</b>	-20, °F -4

(See section 16 for abbreviation legend)

<u>CHEMICAL NAME</u>	<u>VAPOR DENSITY</u>	<u>EVAPORATION RATE</u>	<u>BOILING POINT</u>	<u>VP mmHg</u>	<u>at DEG. F</u>
ACETONE	2.00	14.40	133	226.00	68

AROMATIC PETROLEUM DISTILATES	4.00	0.09	354	1.00	68
TOLUENE	3.20	2.00	233	16.70	68
METHANOL	1.11	5.20	149	47.30	77

## Section 10. Stability and reactivity

**STABILITY:** Stable under normal conditions.

**CONDITIONS TO AVOID:** Avoid contact with skin, eyes and clothing.

**INCOMPATIBILITY:** Keep away from strong oxidizing agents, heat and open flames.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon Monoxide, Carbon Dioxide

## Section 11. Toxicological information



### Practical Experiences

**EFFECT OF OVEREXPOSURE - INHALATION:** Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Direct eye contact may cause irritation.

**EFFECT OF OVEREXPOSURE - INGESTION:** Harmful: may cause lung damage if swallowed. Harmful: possible risk of irreversible effects if swallowed. May be fatal or cause blindness.

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
67-64-1	ACETONE	N.I.	N.I.	N.I.
64742-94-5	AROMATIC PETROLEUM DISTILATES	N.I.	N.I.	N.I.
108-88-3	TOLUENE	5580	12196	12500
67-56-1	METHANOL	N.I.	N.I.	N.I.

N.I. - No Information

## Section 12. Ecological information

**ECOLOGICAL INFORMATION:** Do not contaminate ponds, waterways or ditches with chemical or used container.

## Section 13. Disposal considerations



### Product

**DISPOSAL METHOD:** Contact waste disposal services.

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Soak up with inert absorbent material and dispose of as hazardous waste.

## Section 14. Transport information

**SPECIAL TRANSPORT PRECAUTIONS:** No Information Page 4 / 7

DOT Proper Shipping Name: Paint, Flammable Liquid  
DOT Technical Name: Paint  
DOT Hazard Class: 3  
DOT UN/NA Number: 1263

Packing Group: II  
Hazard SubClass: No Information  
Resp. Guide Page: 128

## Section 15. Regulatory information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### SARA SECTION 312:

<u>Chemical Name</u>	<u>CAS-No.</u>
ACETONE	67-64-1
AROMATIC PETROLEUM DISTILATES	64742-94-5
TOLUENE	108-88-3
METHANOL	67-56-1

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
TOLUENE	108-88-3
NAPHTHALENE	91-20-3
METHANOL	67-56-1
1,2,4 TRIMETHYLBENZENE	95-63-6

#### TOXIC SUBSTANCES CONTROL ACT:

All components of this material are listed on the US Toxic Substance Control Act (TSCA inventory).

### U.S. State Regulations:

#### NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
CALCIUM CARBONATE	1317-65-3
BUTYL METHACRYLATE COPOLYMER	28262-63-7
MONOAZO YELLOW	6358-31-2

#### PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
CALCIUM CARBONATE	1317-65-3
BUTYL METHACRYLATE COPOLYMER	28262-63-7

#### CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

**Chemical Name**

NAPHTHALENE

**CAS-No.**

91-20-3

**CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

**Chemical Name**

TOLUENE

METHANOL

**CAS-No.**

108-88-3

67-56-1

**International Regulations: As follows -****CANADIAN WHMIS:**

All components of this material are listed on the Domestic Substance List.

WHMIS Class: No Information

**Section 16. Other information, including date of preparation of the last revision**

Revision Date: 3/9/2016 Supersedes Date: New MSDS  
Reason for revision: GHS  
Datasheet produced by: Regulatory Department

**HMIS Ratings:**

<b>Health:</b>	2	<b>Flammability:</b>	3	<b>Reactivity:</b>	0	<b>Personal Protection:</b>	X
----------------	---	----------------------	---	--------------------	---	-----------------------------	---

Volatile Organic Compounds, gr/ltr: 98\*

**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

H225	Highly flammable liquid and vapour.
H227	Combustible liquid
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H320	Causes eye irritation
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H361	Suspected of damaging fertility or the unborn child.
H370	Causes damage to organs . Classified Category 1 Substances that produced significant toxicity in humans and evidence to produce significant toxicity with single exposure. Cell death, adverse change in biochemistry, haematology or urinalysis parameters, Central or peripheral nervous system and effects senses. multifocal or diffuse necrosis, fibrosis or granuloma formation in organs.
H373	May cause damage to organs through prolonged or repeated exposure.

**Icons for GHS Pictograms shown in Section 3 describing each ingredient:**

GHS02



GHS06



GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information No Information

\*Please note: Prior to March 8, 2016, this product's VOC's were greater than 100 grams per liter.