

TACK AWAY

SMT-335

REVISED 07/22/21

PRODUCT DESCRIPTION & BENEFITS

Tack Away is a liquid detackifier for hot-applied crack sealants.

- Prevents tracking of freshly applied hot pour crack sealants
- Eliminates stickiness of freshly applied sealant
- Provides a barrier between tires and fresh sealant
- Compatible with all hot pour crack sealants (Will not attack or harm sealant)
- Reduces traffic down time
- Economical and time saving
- Will not alter or affect sealant properties
- Environmentally-friendly and biodegradable

SIZES

Available in 5-gallon pails.

METHODS

Tack Away can be applied by spray.

MIXING/APPLICATION PROCEDURES

Gently stir Tack-Away prior to use. Fill Garden-type, hand-held pump up sprayer with Tack-Away. Adjust spray tip to a medium fan pattern. Spray Tack-Away directly on freshly applied crack sealant while minimizing overspray onto pavement.

COVERAGE

One gallon of Tack-Away will cover from 1,000 to 2,000 feet of cracks depending upon rate of application.

CLEAN UP

Tack-Away cleans up with water. Run water through sprayer when finished with application of Tack-Away.

SAFETY

Do not ingest. Avoid contact with eyes. Wear non-pervious gloves and eye protection when working with Tack-Away.

FIRST AID

IN EYE: Immediately flush with large amounts of water for 15 minutes. If needed, seek medical attention. **IF INGESTED:** Do not induce vomiting. Seek immediate medical attention. **ON SKIN:** Wash with soap and water.

CAUTION

PROTECT CONTAINER FROM FREEZING. TACK-AWAY IS A WATER-BASED PRODUCT.
KEEP OUT OF REACH OF CHILDREN.

WARRANTY AND DISCLAIMER

The statements made on this technical data sheet are

believed to be true and accurate and are intended to provide a guide for approved application practices. As workmanship, weather, construction, condition of pavement, tools utilized, and other variables affecting results are all beyond our control, the manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. The manufacturer expressly disclaims any implied warranties of merchantability or fitness for a particular purpose.