

## TACK-IT

**SMT-223**

REVISED 3/19/24

### PRODUCT DESCRIPTION & BENEFITS

A bituminous joint sealant and tack coat designed as an adhesion promoter and water-proofer.

### USES

- Paving Joints
- Asphalt Patch Work
- Adhesion Promoter
- Waterproofing
- Roof Repairs
- Manhole Cover Edges
- Sewer Grate Edges
- Utility Cuts
- And More

### COMPOSITION

Tack-It is comprised of asphalt, solvents, and petroleum gas.

### SIZES

Available in a 17 fl. oz spray can.

### COLOR

Dries Black.

### INSTALLATION

Surface must be cleaned of dust, dirt and debris.

1. Remove standing water and debris. Can be applied to damp surfaces.
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Invert can and press button. Hold can 8-12 inches above surface and spray using long even strokes.
4. When finished spraying, immediately turn can upward and spray for a few seconds to clear out spray tip for later use.
5. Completely empty cans may be disposed of with regular trash. DO NOT incinerate or compact.

### ESTIMATING MATERIAL REQUIREMENTS

For use as a primer, approximately 33 sq. ft. per 17 fl. oz. can, depending on pavement porosity and condition.

### PRECAUTIONS

For exterior use only. Do not use in drinking water or food systems. For longest life, store in controlled environment, 50°F to 85°F.

**DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR HARMFUL/ MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. KEEP OUT OF REACH OF CHILDREN.** Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting.

Do not expose to heat or store at temperatures above 120°F (49°C).

### WARRANTY AND DISCLAIMER

The statements made on this technical data sheet are believed to be true and accurate and are intended to provide a guide for approved application practices. As workmanship, weather, construction, condition of pavement, tools utilized, and other variables affecting results are all beyond our control, the manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. The manufacturer expressly disclaims any implied warranties of merchantability or fitness for a particular purpose.

Copyright © InFrasys, Inc. All rights reserved. Reproduction of any of this material is strictly prohibited.