

ACRYLIC CRACK PATCH

CMT-7

REVISED 12/19

PRODUCT DESCRIPTION & BENEFITS

Acrylic Crack Patch is a 100% acrylic trowel grade crack filler designed for filling cracks or damaged areas in asphalt or concrete surfaces, up to 1" wide.

USES

Asphalt or concrete tennis courts, basketball courts, pickleball courts, play areas, and all-purpose sport surfaces.

COLOR

Available in green, red, neutral and blue.

Chemical Characteristics	
	% Weight (minimum)
Acrylic Emulsion	10.0
Hiding Pigment	.2
Mineral Inert Fillers	78.0
Film Formers, Additives	1.8
Water	8.5

Product Data	
Type	Acrylic Emulsion
Pounds per gallon at 77°F	15.2 ± 1
% Non Volatile Material	80 ± 5
Odor	Slight Ammonia
Flammability	Non-Flammable
Flash Point	None
Storage Life	One Year
Colors	Several Available

SURFACE PREPARATION

Cracks must be cleaned of dust, dirt, and debris including vegetation. Blow clean with air compressor or high pressure washer.

MIXING PROCEDURES

Use as is. DO NOT DILUTE.

APPLICATION

Work Acrylic Crack Patch down into crack using rectangular trowel or putty knife. Wipe off excess material with damp cloth before it dries to prevent material buildup on court surface.

IMPORTANT

Surface and air temperatures must be above 50°F (10°C) during application and for at least 24 hours after application. Stir before using. Do not apply when rain is imminent or forecast. Keep from freezing. Close container when not in use.

DRYING TIME

1 hour up to a full day, depending on width and depth of the repair, as well as weather and surface conditions.

COVERAGE

Typically one gallon will fill approximately 75-150 feet of cracks depending on depth and width of crack.

CAUTIONS

Do not store in direct sunlight or where temperatures exceed 100°F. Do not apply if rain is imminent or forecast. Keep from freezing. Close container when not in use. Refer to product Safety Data Sheet (SDS) for additional safety information and precautions.

WARRANTY

The statements made on this technical bulletin are believed to be true and accurate, and are intended to provide a guide for approved construction practices. Manufacturer does not make, nor does it authorize any agent or representative to make any warranty, express or implied, concerning this material as workmanship, weather, construction, equipment utilized and other variables affecting results are all beyond our control. Manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. In no event shall Manufacturer be liable for any injury, loss or damage, either direct or incidental, special or consequential, however arising, in connection with material or equipment furnished or work performed. Manufacturer shall not, in any manner, be liable for any defects, variations or change in condition in the substructure over which its products are installed.

Copyright © InFrasys, Inc. All rights reserved. Reproduction of any of this material is strictly prohibited.

ThorWorks Industries, Inc.
P.O. Box 2277
Sandusky, OH 44870

Phone: 1-800-326-1994
FAX: 1-419-626-5477
www.sportmaster.net